

TECHNICAL DATA SHEET

SUPER-EGO

HEAVY DUTY EXPERIENCE

PRODUCT: ROMASSGAS CARTRIDGE
REFERENCE: SEH024600

Revision date 7/6/2024

Revision No. 2

In accordance with Annex II of REACH - Regulation (EU) 2020/878

SECTION 1. Identification of the substance/mixture and of the company/undertaking 1.1.

Code: SEH024600
Product name: ROMASSGAS CARTRIDGE
Chemical name and synonym: Hydrocarbons, rich in C3-C4, petroleum distillate
INDEX number: 649-083-00-0
EC number: 270-990-9
CAS number: 68512-91-4
Registration Number: 02-2119737773-30-0000

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: Camping gas cartridge. For use only in portable gas appliances

1.3. Details of the supplier of the safety data sheet

Name: SUPER-EGO TOOLS, S. L.U.
Full address: Ctra. Durango –Elorrio, Km 2
District and Country: 48220 Abadiño (Bizkaia)
ESPAÑA (SPAIN)
Tel. + 34 946 210 100
Fax. + 34 946 210 131
e-mail address of the competent person responsible for the Safety Data Sheet: seguridad@super-ego.es
Supplier: SUPER-EGO TOOLS, S. L.U.

1.4. Emergency telephone number

For urgent inquiries refer to: Instituto Nacional de Toxicología (Madrid), 91 5620420

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The substance has been evaluated and/or tested for its physical hazards and hazards to health and the environment, and the following classification applies.

Classification according to Regulation (EC) No. 1272/2008 (CLP) and its subsequent amendments

Physical hazards

Flammable gases: Category 1A, H220 - Extremely flammable gas.

Pressurized gases: Liquefied gas, H280 - Contains gas under pressure; danger of explosion if heated. heating.

2.2. Label elements Labeling according to Regulation (EC) No. 1272/2008 and its subsequent amendments

Danger pictograms



Warning word

Danger

Indications of danger

H220
H280

Extremely flammable gas.
Contains gas under pressure; danger of explosion if heated.

TECHNICAL DATA SHEET

SUPER-EGO

HEAVY DUTY EXPERIENCE

PRODUCT: ROMASSGAS CARTRIDGE
REFERENCE: SEH024600

Revision date 7/6/2024

Revision No. 2

In accordance with Annex II of REACH - Regulation (EU) 2020/878

Cautionary advice

Prevention

P210 Keep away from heat, hot surfaces, sparks, open flames and other sources of ignition. Do not smoke.
P233 Keep container tightly closed.

Reply

P377 Burning gas leak: Do not extinguish unless leak can be stopped safely. In case of leakage, eliminate all sources of ignition.
P381

Storage

P410 + P403 Protect from sunlight. Store in a well-ventilated place.
Not assigned.

Disposal

None.
May replace oxygen and cause rapid asphyxiation.

Additional information which must appear on the label

2.3. Other Hazards

Contact with liquefied gas may cause frostbite.
This substance does not meet the vPvB / PBT criteria of Regulation (EC) No 1907/2006, Annex XIII.

The substance is not included in the list established in accordance with Article 59(1) of REACH due to endocrine disrupting properties.
The substance is not considered to have endocrine disrupting properties according to the criteria set out in the Commission Delegated Regulation (EU) 2017/2100 or Regulation (EU) 2018/605/EC.
Commission Regulation (EU) 2018/605.

SECTION 3. Composition/information on ingredients

3.1. Substances

General information

Chemical name

propylene

%

99.5-100

CAS Number / EC Number

115-07-1

204-062-1

REACH Registration

Number

01-2119447103-50-0287

Classification

Flam, Gas 1; H220, Press. Gas; H280

SECTION 4. First aid

4.1. First aid description

Inhalation

Leave the site to avoid further exposure. Those providing assistance should avoid exposing themselves and others. Wear appropriate respiratory protection. If respiratory tract irritation, dizziness, nausea or loss of consciousness occurs, seek immediate medical attention. If respiratory arrest has occurred, help ventilate lungs with a mechanical device or perform mouth-to-mouth resuscitation maneuver.

Skin contact

Unlikely due to the form of the product. If freezing damage occurs, immerse affected area in warm water (not to exceed 105°F/41°C). Keep submerged for 20 to 40 minutes. Obtain medical assistance.

Eye contact

Unlikely due to the shape of the product. If localized frostbite occurs, immediately flush eyes with copious amounts of warm water (not to exceed 105 °F / 41°C) for at least 15 minutes. If easy to do, remove contact lenses. Get medical attention immediately if symptoms persist or arise after flushing.

Ingestion

This material is a gas under normal atmospheric conditions and ingestion is not considered likely.

TECHNICAL DATA SHEET

SUPER-EGO

HEAVY DUTY EXPERIENCE

PRODUCT: ROMASSGAS CARTRIDGE
REFERENCE: SEH024600

Revision date 7/6/2024
Revision No. 2

In accordance with Annex II of REACH - Regulation (EU) 2020/878

4.2. Main symptoms and acute and delayed effects

Exposure to rapidly expanding gas or vaporizing liquid may cause frostbite ("freezer burn"). Very high exposure may result in asphyxiation due to lack of oxygen. Symptoms may include loss of mobility/consciousness. Victim may not notice asphyxiation. Asphyxiation may cause unconsciousness without warning and so quickly that people can do nothing to protect themselves.

4.3. Indication of any medical care and any special treatments that should be dispensed immediately

Exposure may aggravate pre-existing respiratory disorders. Provide general supportive measures and symptomatic treatment.

SECTION 5. Fire fighting measures

General fire hazards

5.1. Suitable extinguishing media

Unsuitable extinguishing media

Extremely flammable gas. Contents under pressure. Pressurized container may explode when exposed to heat or flame. Dry chemical powder. Carbon dioxide (CO2). Water mist. Foam. Do not use water jet, as it will spread the fire.

5.2. Specific hazards arising from the substance or mixture

Extremely flammable gas. May form explosive mixtures with air. Vapors may travel a fairly long distance to a source of ignition and ignite. In case of fire, noxious gases may be formed.

5.3. Recommendations for firefighting personnel

Special protective equipment to be worn by firefighters

Wear self-contained breathing apparatus and full protective suit in case of fire.

Special firefighting procedures

Do not extinguish fire unless gas flow can be safely stopped; explosive reignition may occur. Immediately isolate the area and evacuate all personnel near the incident. Do not initiate actions that pose a risk to people or without proper training. In case of fire involving this material, do not enter enclosed or confined spaces with fire without using appropriate protective equipment, including self-contained breathing apparatus. Stop the flow of material. Use water to keep fire-exposed containers cool and protect personnel shutting off service. If a leak or spill has not ignited, use water spray to disperse vapors and protect personnel. disperse vapors and protect personnel trying to shut off the leak. Prevent runoff water from fire control or dilution from entering streams, sewers or drinking water supplies.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials. Cool fire-exposed containers with water until well after the fire has ceased.

TECHNICAL DATA SHEET

SUPER-EGO

HEAVY DUTY EXPERIENCE

PRODUCT: ROMASSGAS CARTRIDGE
REFERENCE: SEH024600

Revision date 7/6/2024
Revision No. 2

In accordance with Annex II of REACH - Regulation (EU) 2020/878

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures.

For non-emergency services personnel

Evacuate the area promptly. Keep unnecessary personnel away. Wear appropriate personal protective equipment.

For emergency personnel

Do not take action involving personal risk or without proper training. In case of leak, evacuate all personnel until ventilation system restores oxygen concentrations to safe levels. Eliminate all ignition sources (no smoking, flares, sparks or flames in the vicinity). Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate enclosed spaces before entering. Wear appropriate protective equipment and clothing during cleanup.

6.2. Environmental Precautions

Must not be released into the environment. Prevent further leakage or spillage in a safe manner. Eliminate all ignition sources (no smoking, flares, sparks or flames in the vicinity).

6.3. Methods and material for containment and cleaning up

Keep combustible materials (wood, paper, oil, etc.) away from spilled material. Stop the leak if you can do so without risk. If possible, turn leaking containers upside down to release gas instead of liquid. Confine the area until the gas is dispersed.

Reference to other sections

Refer to personal protective measures in section 8 of the SDSM. For disposal information, see section 13.

SECTION 7. Handling and storage

7.1. Precautions for Safe Handling

Keep away from heat, sparks, open flame or hot surfaces. - Do not smoke. Do not handle, store or open near open flame, heat sources or sources of ignition. Protect material from direct sunlight. Do not smoke. All equipment used in handling the product must be grounded. Do not breathe gas. Avoid prolonged exposure. Do not enter storage areas or enclosed spaces unless adequately ventilated. Use only outdoors or in a well-ventilated area. Oxygen concentration should not fall below 19.5% at sea level (pO₂ = 135 mm Hg). May require forced ventilation or local exhaust ventilation. Wear appropriate personal protective equipment. Observe regulations for proper handling of chemicals.

7.2. Conditions for safe storage, including possible incompatibilities

Do not store, incinerate or heat this material above 48.9 degrees Celsius. Store away from heat, sparks or naked flames. This material may accumulate static charges which can cause sparks and become a source of ignition. Prevent electrostatic charges from building up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Cylinders should be stored upright, with the protective valve cap in place, and firmly secured to prevent them from falling or being knocked over. Protect the cylinders from damage. Stored containers should be checked periodically for general condition and possible leaks. Store in the original container tightly closed. Store in a well ventilated area. Keep away from incompatible materials (see section 10 of the SDS). Directive 2012/18/EU on major-accident hazards involving dangerous substances and its subsequent amendments.

7.3. Specific end uses

ANNEX 1, PART 1 Categories of Dangerous Substances
Hazard categories according to Regulation (EC) No. 1272//2008
-P2 FLAMMABLE GASES (lower tier requirements = 10 t; upper tier requirements = 50 t)
ANNEX 1, PART 2 Nominated Dangerous Substances
Liquefied flammable gases of category 1 or 2 (including LPG) and natural gas (lower tier requirements = 50 t; upper tier requirements = 200 t)
Hand torch fuel. Follow industry best practice instructions.

TECHNICAL DATA SHEET

SUPER-EGO

HEAVY DUTY EXPERIENCE

PRODUCT: ROMASSGAS CARTRIDGE
REFERENCE: SEH024600

Revision date 7/6/2024

Revision No. 2

In accordance with Annex II of REACH - Regulation (EU) 2020/878

SECTION 8. Exposure controls/individual protection

8.1. Control parameters

Occupational exposure limits

Environmental limit values (ELVs)

Material	Type	Value
Propylene (CAS 115-07-1)	VLA-ED	500 ppm

Biological limit values

There are no biological exposure limits for the ingredient(s).

Monitoring methods recommended

Follow standard monitoring procedures.

Derived no-effect levels (DNEL)

Not available.

Predicted No Effect Concentrations (PNECs)

Not available.

Exposure Guidelines

Follow standard monitoring procedures.

8.2. Exposure controls

Appropriate engineering controls

Provide adequate ventilation and minimize the risk of gas inhalation. Isolate the process, use local mechanical ventilation, or any engineering control method to keep airborne levels below recommended exposure limits.

Individual protective measures, such as personal protective equipment

General information

Use the mandatory personal protective equipment. Personal protective equipment shall be chosen in accordance with the CEN standard in force and in collaboration with the supplier of personal protective equipment.

Eye/face protection

Use approved safety glasses. Protective face shields are recommended. Eye protection must comply with EN 166.

Skin protection -Hand protection -Other

Wear suitable gloves tested according to EN 374. Wear gloves that insulate against the cold. Wear protective clothing suitable for the risk of exposure.

Respiratory protection

If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or at an acceptable level (in countries where exposure limits have not been established), an approved respirator should be used. Use positive pressure self-contained breathing apparatus (SCBA).
WARNING! Air-purifying respirators do not protect workers in oxygen deficient atmospheres.

Thermal hazards

Contact with liquefied gas may cause frostbite, in some cases with tissue injury. Wear suitable thermal protective clothing if necessary.

Hygiene measures

Do not eat, drink or smoke while using the product. Wash thoroughly after handling. Provide eye wash station and emergency shower. Handle in accordance with good industrial hygiene and safety practices.

Environmental exposure controls

Check that emissions from ventilation equipment or work processes are in accordance with environmental protection regulations. To reduce emissions to acceptable levels, it may be necessary to use fume scrubbers or filters or modify the design of process equipment.

TECHNICAL DATA SHEET

SUPER-EGO

HEAVY DUTY EXPERIENCE

PRODUCT: ROMASSGAS CARTRIDGE
REFERENCE: SEH024600

Revision date 7/6/2024

Revision No. 2

In accordance with Annex II of REACH - Regulation (EU) 2020/878

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Gas.
Form	Compressed liquefied gas.
Color	Colorless.
Odor	Hydrocarbon or mercaptan if odorous.
Olfactory threshold	Property has not been measured.
Melting point/freezing point	-185 °C (-301 °F)
Boiling point or initial boiling point or initial boiling point and boiling range	-48 °C (-54.4 °F)
Flammability	Extremely flammable gas.

Upper/lower flammability or explosion limits

Lower explosive limit (%)	2 %
Upper explosive limit (%)	11 %

Flash point	-107.78 °C (-162 °F)
Auto-ignition temperature	497.22 °C (927 °F)
Decomposition temperature decomposition temperature	The property has not been measured.
pH	Not applicable, material is a gas.
Kinematic viscosity Solubility	Not applicable, material is a gas.
Solubility (water)	384 mg/l Slightly soluble in water.
Partition coefficient (n-octanol/water) (log value)	1,77
Vapor pressure	109,73 psig (21 °C (69,8 °F))
Density and/or relative density	1,5 (gas) (Aire = 1) (20 °C (68 °F)) 0,52 (líquido) (Agua=1) (0 °C (32 °F))
Densidad de vapor	The property has not been measured.
Características de las partículas	
Tamaño de partícula	Not applicable, material is a gas.

9.2. Other information

9.2.1. Information relating to the physical hazard classes	No additional relevant information is available.
---	--

TECHNICAL DATA SHEET

SUPER-EGO

HEAVY DUTY EXPERIENCE

PRODUCT: ROMASSGAS CARTRIDGE
REFERENCE: SEH024600

Revision date 7/6/2024

Revision No. 2

In accordance with Annex II of REACH - Regulation (EU) 2020/878

9.2.2. Other safety features

Dynamic viscosity	0,08 mPa.s (16,7 °C (62,06 °F))
Evaporation rate	The property has not been surveyed.
Oxygen Limit	
Concentration (OLC)	9,3 %
Molecular formula	C3-H6
Molecular weight	45 g/mol
Percentage of volatiles	100 %
Relative density	1,5 (gas) (Aire = 1) (15 °C (59 °F)) 0,52 (líquido)
Surface tension	16,7 mN/m (90 °C (194 °F))
Viscosity	Not applicable, material is a gas.
VOC	100 % EPA stimated

SECTION 10. Stability and reactivity

10.1. Reactivity	Reacts violently with strong oxidizers, nitrites, as well as inorganic chlorides, chlorites and perchlorates, with risk of fire and explosion.
10.2. Chemical stability	Stable at normal temperatures and for recommended use.
10.3. Possibility of hazardous reactions	No polymerization occurs. May form explosive mixtures with air. This product may react with oxidizing agents.
10.4. Conditions to avoid	Avoid heat, sparks, open flames and other sources of ignition. Avoid temperatures above the flash point. Contact with incompatible materials.
10.5. Incompatible materials	Strong oxidizing agents. Strong acids. Halogens. Nitrates.
10.6. Hazardous decomposition products	Thermal decomposition of this product may generate carbon monoxide and carbon dioxide. Hydrocarbons.

TECHNICAL DATA SHEET

SUPER-EGO

HEAVY DUTY EXPERIENCE

PRODUCT: ROMASSGAS CARTRIDGE
REFERENCE: SEH024600

Revision date 7/6/2024
Revision No. 2

In accordance with Annex II of REACH - Regulation (EU) 2020/878

SECTION 11. Toxicological information

General information Occupational exposure to the substance or mixture may have adverse effects.

on possible routes of exposure

Inhalation EIn high concentrations: Suffocation hazard (asphyxiant) - if allowed to accumulate at concentrations that reduce oxygen below safe breathing levels. Inhalation of high concentrations may cause dizziness, dullness, headache, nausea and loss of coordination. Continuous inhalation may cause loss of consciousness.

Skin contact Contact with liquefied gas may cause frostbite.

Eye contact Contact with liquefied gas may cause freezing.

Ingestion This material is a gas under normal atmospheric conditions, and ingestion is not considered likely.

Symptoms Exposure to rapidly expanding gas or vaporizing liquid may cause frostbite ("freezer burn"). Very high exposure may result in asphyxiation due to lack of oxygen. Symptoms may include loss of mobility/consciousness. Victim may not notice asphyxiation. Suffocation can cause unconsciousness without warning and so quickly that people can do nothing to protect themselves.

11.1. Information on hazard classes as defined in Regulation (EC) No. 1272/2008

Acute Toxicity No se espera que tenga toxicidad aguda.

Toxicological data

Impurities	Species	Test results
Propane (CAS 74-98-6)		
Acute Inhalation		
Gas	Rat	>80000 ppm, 15 Minutes
CL50		

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation Based on available data, the classification criteria are not met.

Respiratory sensitization Based on available data, the classification criteria are not met.

Skin sensitization Based on available data, the classification criteria are not met.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

IARC Monographs. General evaluation of carcinogenicity

propylene (CAS 115-07-1) 3 Not classifiable as to carcinogenicity to humans.

Reproductive toxicity Based on available data, the classification criteria are not met.

Specific target organ toxicity - single exposure Based on available data, the classification criteria are not met.

Specific target organ toxicity - repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

Information on the mixture related to the substance Not relevant due to the shape of the product.

11.2 Information on other hazards

TECHNICAL DATA SHEET

SUPER-EGO

HEAVY DUTY EXPERIENCE

PRODUCT: ROMASSGAS CARTRIDGE
REFERENCE: SEH024600

Revision date 7/6/2024

Revision No. 2

In accordance with Annex II of REACH - Regulation (EU) 2020/878

Endocrine disrupting properties This substance does not have endocrine disrupting properties related to human health as it does not meet the assessment criteria set out in Regulations (EC) No. 1907/2006, (EU) No. 2017/2100 and (EU) 2018/605.

Additional information Long-term exposure may cause damage to the nervous system.

SECTION 12. Ecological information

12.1. Toxicity	The product is assumed to have no negative effects on the environment.
12.2. Persistence and degradability	Not relevant due to the form of the product.
12.3. Bioaccumulative Potential	Not relevant due to the form of the product.
Partition coefficient n-octanol/water (log Kow)	
propylene (CAS 115-07-1)	1,77
Bioconcentration factor (BCF)	Not available.
12.4. Mobility in soil	Not relevant due to the form of the product.
12.5. Results of PBT and vPvBm assessment	This substance does not meet the vPvB / PBT criteria of Regulation (EC) No 1907/2006, Annex XIII.
12.6. Endocrine disrupting properties	This substance does not have endocrine disrupting properties related to the environment as it does not meet the assessment criteria set out in Regulations (EC) No 1907/2006, (EU) No 2017/2100 and (EU) 2018/605.
12.7. Other adverse effects	The product contains volatile organic compounds that may contribute to photochemical ozone creation.

Global warming potential of the substance according to (Annex IV), Regulation 517/2014/EU on fluorinated greenhouse gases, as amended.

propylene (CAS 115-07-1)

SECTION 13. Disposal Considerations

13.1. Waste Treatment Methods	
Product residues	Dispose in accordance with all applicable regulations.
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal.
European Waste Code	16 05 04* Waste code should be assigned by agreement between user, producer and waste disposal company.
Methods of disposal/information	Use the container until it is empty. Do not dispose of containers that are not empty. Empty containers retain residual vapors that are flammable and explosive. Cylinders should be emptied and returned to a hazardous waste collection point. Should not be punctured or burned, even after use. Dispose in accordance with all applicable regulations.
Special precautions	Dispose of in accordance with local regulations.

TECHNICAL DATA SHEET

SUPER-EGO

HEAVY DUTY EXPERIENCE

PRODUCT: ROMASSGAS CARTRIDGE
REFERENCE: SEH024600

Revision date 7/6/2024
Revision No. 2

In accordance with Annex II of REACH - Regulation (EU) 2020/878

SECTION 14. Transport information

ADR

14.1. Número ONU UN1077
14.2. Designación oficial de transporte de las Naciones Unidas PROPILENO
14.3. Clase(s) de peligro para el transporte

Clase	2.1
Riesgo subsidiario	-
Label(s)	2.1
No. de riesgo (ADR)	23
Código de restricción en túneles	B/D

14.4. Grupo de embalaje

14.5. Peligros para el medio ambiente

14.6. Precauciones particulares para los usuarios Lea las instrucciones de seguridad, la FDS y los procedimientos de emergencia antes de manejar el producto.

RID14.1. Número ONU

14.2. Designación oficial de transporte de las Naciones Unidas UN1077 PROPILENO

14.3. Clase(s) de peligro para el transporte

Clase	2.1
Riesgo subsidiario	-
Label(s)	2.1 (+13)

14.4. Grupo de embalaje

14.5. Peligros para el medio ambiente

14.6. Precauciones particulares para los usuarios Lea las instrucciones de seguridad, la FDS y los procedimientos de emergencia antes de manejar el producto.

ADN

14.1. Número ONU UN1077
14.2. Designación oficial de transporte de las Naciones Unidas PROPILENO

14.3. Clase(s) de peligro para el transporte

Clase	2.1
Riesgo subsidiario	-
Label(s)	2.1

14.4. Grupo de embalaje

14.5. Peligros para el medio ambiente

14.6. Precauciones particulares para los usuarios Lea las instrucciones de seguridad, la FDS y los procedimientos de emergencia antes de manejar el producto.

TECHNICAL DATA SHEET

SUPER-EGO

HEAVY DUTY EXPERIENCE

PRODUCT: ROMASSGAS CARTRIDGE
REFERENCE: SEH024600

Revision date 7/6/2024

Revision No. 2

In accordance with Annex II of REACH - Regulation (EU) 2020/878

IATA

14.1. UN number UN1077
14.2. UN proper shipping name Propylene
14.3. Transport hazard class(es)
 Class 2.1
 Subsidiary risk -
 Label(s) 2.1
14.4. Packing group -
14.5. Environmental hazardsNo
ERG Code 10L
14.6. Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IMDG

14.1. UN number UN1077
14.2. UN proper shipping name PROPYLENE
14.3. Transport hazard class(es)
 Class 2.1
 Subsidiary risk -
14.4. Packing group -
14.5. Environmental hazardsNo
 Marine pollutant F-D, S-U
 EmS Read safety instructions, SDS and emergency procedures before handling.
14.6. Special precautions for user No aplicable.

14.7. Transporte marítimo a granel con arreglo a los instrumentos de la OMI

PRODUCT: ROMASSGAS CARTRIDGE
REFERENCE: SEH024600

Revision date 7/6/2024
Revision No. 2

In accordance with Annex II of REACH - Regulation (EU) 2020/878

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations and legislation specific to the substance or mixture EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annexes I and II, and subsequent amendments.

Not listed.

Regulation 2019/1021 (EU) on persistent organic pollutants (recast), as amended.

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1, as amended.

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2, as amended.

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3, as amended.

Not listed.

Regulation (EU) No 649/2012 concerning the export and import of dangerous chemicals, Annex V and subsequent amendments thereto.

Not listed.

Regulation (EC) No. 166/2006, Annex II, Pollutant Release and Transfer Register, as amended.

Not listed.

Regulation (EC) No. 1907/2006, REACH Article 59(10), List of Candidates in force published by ECHA

Not listed.

Authorizations

Regulation (EC) No. 1907/2006 REACH, Annex XIV Substances subject to authorization, as subsequently amended.

Not listed.

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII, Substances subject to marketing and use restrictions with subsequent amendments

propylene (CAS 115-07-1)

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens or mutagens at work and subsequent amendments.

Not listed.

Other EU standards

Directive 2012/18/EU on major-accident hazards involving dangerous substances and subsequent involving dangerous substances and its subsequent amendments

ANNEX 1, PART 1 Hazardous substances categories.

Hazard categories in accordance with Regulation (EC) No. 1272/2008

-P2 FLAMMABLE GASES

ANNEX 1, PART 2 Nominated Dangerous Substances

-18. Flammable liquefied gases of category 1 or 2 (including LPG) and natural gas

TECHNICAL DATA SHEET

SUPER-EGO

HEAVY DUTY EXPERIENCE

PRODUCT: ROMASSGAS CARTRIDGE
REFERENCE: SEH024600

Revision date 7/6/2024

Revision No. 2

In accordance with Annex II of REACH - Regulation (EU) 2020/878

Directive 2012/18/EU on major-accident hazards involving dangerous substances, as subsequently amended.

Propane (CAS 74-98-6)
propylene (CAS 115-07-1)

Other regulations

This product has been classified and labeled in accordance with Regulation (EC) No. 1272/2008 (CLP Regulation) as subsequently amended and in accordance with. This safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006 as amended.

National regulations

Observe national regulations concerning work with chemical agents in accordance with Directive 98/24/EC as amended.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

TECHNICAL DATA SHEET

SUPER-EGO

HEAVY DUTY EXPERIENCE

PRODUCT: ROMASSGAS CARTRIDGE
REFERENCE: SEH024600

Revision date 7/6/2024

Revision No. 2

In accordance with Annex II of REACH - Regulation (EU) 2020/878

SECTION 16. Other information

List of abbreviations

ADN: European Agreement concerning the international carriage of dangerous goods by inland waterways. ADR: Agreement concerning the International Carriage of Dangerous Goods by Road. CAS: Chemical Abstract Service (Chemical Abstract Service). CEN: European Committee for Standardization. IATA: International Air Transport Association IBC Code: International Code for the International Carriage of Dangerous Goods by Road. IBC Code: International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk. IMDG: International Maritime Dangerous Goods Code. MARPOL: International Convention for the Prevention of Pollution from Ships. PBT: Persistent, Bioaccumulative and Toxic. RID: Regulations concerning the International Carriage of Dangerous Goods by Rail. STEL: Short Term Exposure Limit. TWA: Time Weighted Average. vPvB: very persistent and very bioaccumulative. ACGIH documentation of threshold limit values and biological exposure indexes. ECHA: European Chemicals Agency. EPA: AQUIRE database HSDB® - Hazardous Substances Database IARC Monographs. Global Assessment of Carcinogenicity. US National Toxicology Program (NTP) Report on Carcinogens NLM: Hazardous Substances database

Not applicable. The product is a substance.

References

Information on the evaluation method used for the classification of the mixture.

Full text of warnings that are not complete in sections 2 to 15

H220 Extremely flammable gas. H280 Contains gas under pressure; danger of explosion if heated.

Information on training

Follow training instructions when handling this material.

Disclaimer of liability clause

All information in this Safety Data Sheet is believed to be accurate and reliable. No However, no warranties or assurances of any kind are made as to the accuracy of the information or the suitability of the recommendations contained herein. It is the responsibility of the user to evaluate the safety and toxicity of this product under his own conditions of use and to comply with all applicable laws and regulations.