

The **NOMAD POWER 801** is a lithium-based power pack combining **3 functions**:

- **Booster pack for 12 V vehicles (cars, SUVs, vans, tractors, boats).**
- **Power bank for powering or charging all electronic devices.**
- **Emergency lamp.**

## LITHIUM BATTERY BOOSTER

The internal lithium battery has an exceptional power-to-size ratio (starting current: 850 A). It can start vehicles with discharged 12 V batteries (liquid, gel, AGM, stop-start) in just a few seconds (⚠ cannot be used to start Lithium LiFePO4 vehicle batteries, as the voltages are not compatible).

START			12 V PETROL & DIESEL			5 > 150 Ah		

## SAFE STARTING

The intelligent starter cable protects both the battery and the electronic equipment in the vehicle:

- Anti-spark technology,
- Short-circuit protection,
- Anti polarity reversal technology.
- Excessive starting current protection,
- Thermal overload protection for the booster.

## MOBILE ENERGY SOURCE

Its impressive storage capacity (5 Ah) offers convenience and reassurance for those who need to stay connected while on the move (phone, tablet, computer).

Equipped with:

- **2 USB ports 5 V - 2.1 A / 5/9/12 V - 2 A + 1 input/output USB Type C for recharging smartphones, tablets, GPS, etc.**
- **1 output port 15 V - 10 A, ideal for camping, to supply a 12 V electrical appliance (cooler, fan, etc.).**

## EMERGENCY LIGHT

Single-LED lamp with 3 lighting modes: normal, strobe, SOS.

## POCKET SIZE

Lightweight (820g) and compact, it fits neatly into the glove compartment or boot of your car, or into a travel bag.



Charging LED



## Supplied with accessories:



Jump lead smart

Charging cable USB type C

## Optional charger unit



087101 15 W USB charger



087354 15 W USB charger

STARTING				EQUIPMENT		INPUT / OUTPUT			POWER BANK	LED	DIMENSIONS			
Lithium			I			SMART CABLE	CABLES	INPUT	OUTPUT		15 V Jack DC	3 modes: Light SOS Strobe	cm	kg
Capacity per cell	Type	Full charge	1 V/C	0 V/C	Peak Battery				USB-C	USB				
5Ah 74 Wh	LiCoO <sub>2</sub>	4 h	850 A	1300 A	1500 A			USB-C 5V - 3A	3	USB 3.0 QC: 5V-2.4A / 9V-2A / 12V-1.5 A USB-A: 5V - 2.1A SB-C: 5V - 3A	10 A		22.8 x 10 x 3.8	0.730