




TABLE OF LOAD ACCORDING TO FORM OF USE

DIRECT SHOT	DOUBLE SHOT	STRANDED	ANGLE FROM 0 TO 45°
x1	x2	x0.8	x1.4



TWO LAYER SLING

The flat sling is a double-layer textile band with a predetermined width, length and color, with reinforced eyes at its ends. This product is an intermediate lifting device for attaching a load to a shackle or lifting hook. In addition, each sling has a product label with a description of all the characteristics to be considered for its correct use. EN1492-1

MATERIAL: 100 % polyester
FINISH: Green color

Part Number	Denomination	Workload W.L.L. (kg) Direct shot	Length L (m)	Band width (mm)	Box Quantity	Outer Box Quantity
09530152	SLGS 2,0x1	2,000	1	60	1	1
09530160	SLGS 2,0x1,5	2,000	1.5	60	1	1
09530179	SLGS 2,0x2	2,000	2	60	1	1
09530187	SLGS 2,0x2,5	2,000	2.5	60	1	1
09530195	SLGS 2,0x3	2,000	3	60	1	1
09530208	SLGS 2,0x3,5	2,000	3.5	60	1	1
09530216	SLGS 2,0x4	2,000	4	60	1	1
09530224	SLGS 2,0x4,5	2,000	4.5	60	1	1
09530232	SLGS 2,0x5	2,000	5	60	1	1
09530240	SLGS 2,0x6	2,000	6	60	1	1
09530259	SLGS 2,0x6,5	2,000	6.5	60	1	1
09530267	SLGS 2,0x8	2,000	8	60	1	1
09530275	SLGS 2,0x10	2,000	10	60	1	1
09530283	SLGS 2,0x12	2,000	12	60	1	1