





TABLE OF LOAD ACCORDING TO FORM OF USE

DIRECT SHOT	DOUBLE SHOT	STRANLED	ANGLE FROM 0 TO 45°
 x1	 x2	 x0.8	 x1.4



TWO LAYER SLING

The flat sling is a double-layer textile band with a predetermined width, length and color, with reinforced eyes at its ends. This product is an intermediate lifting device for attaching a load to a shackle or lifting hook. In addition, each sling has a product label with a description of all the characteristics to be considered for its correct use. EN1492-1

MATERIAL: 100 % polyester
FINISH: Brown color

Part Number	Denomination	Workload W.L.L. (kg) Direct shot	Length L (m)	Band width (mm)	Box Quantity	Outer Box Quantity
09530718	SLGS 6,0x4	6,000	4	180	1	1
09530726	SLGS 6,0x4,5	6,000	4.5	180	1	1
09530734	SLGS 6,0x5	6,000	5	180	1	1
09530742	SLGS 6,0x6	6,000	6	180	1	1
09530750	SLGS 6,0x6,5	6,000	6.5	180	1	1
09530769	SLGS 6,0x8	6,000	8	180	1	1
09530777	SLGS 6,0x10	6,000	10	180	1	1
09530785	SLGS 6,0x12	6,000	12	180	1	1