



25·35·45 Series

IDROPULTRICI ALTA PRESSIONE
high pressure washers

SEMI-PRO



porta accessori
built-in accessories
holder



battistrada in
gomma
rubber wheels



manico ergonomico
ergonomic handle



caldaia in acciaio
Stainless steel boiler



filtro ingresso acqua
ispezionabile
inspectable water
intake filter

Caratteristiche Generali

- Pompa a 3 pistoni assiali comandati da piattello oscillante (2591, 3590) o con sistema biella-manovella (4590)
- Pistoni in acciaio inox temprato
- Valvola di by-pass automatica con azzeramento della pressione nella testa della pompa
- Motore monofase a induzione con protezione termica
- Pressostato di sicurezza per spegnimento della caldaia in caso di mancanza acqua
- Caldaia verticale, doppia serpentina e fondo in materiale refrattario
- Serbatoio gasolio 4 l
- Filtro acqua e filtro aspirazione gasolio
- Tubo rinforzato con treccia in acciaio (8 m)


General Features

- 3 Axial stainless steel pistons wobble-plate pump (2591, 3590) or with connecting rod system (4590)
- Tempered stainless steel pistons
- Automatic by-pass valve with pump head pressure discharge
- Single-phase induction motor with thermal protector
- With safety pressure switch to shut down the boiler in case of lack of water
- Vertical boiler with double heating coil and refractory compound base
- Fuel tank capacity 4 l
- Water filter and fuel inlet filter
- Steel braided reinforced hose (8 m)

2591.3590 4590

HRM

HPV-O



MOD	COD	 MAX	 MAX					 KG NET			
		bar max	psi max	l/h max	gph max	kW	rpm	Hz	V	kg	°C Max
2591	15376-V	140	2030	420	111	2,2	2800	50	230~	48	90
3590	24425-V	150	2175	450	119	2,4	2800	50	230~	52	90
4590	24426-V	160	2320	500	132	2,5	2800	50	230~	52,8	90

Accessori standard / Standard accessories



codice / code	41047	50690	3164470 (8 m)	3729 (2591.3590/15025) 3104 (4590/1503)	40320
entrata inlet	3/8 M	M22x1,5 M	M22x1,5 F	1/4 NPT M	M22x1,5 M
uscita outlet	M22x1,5 F	1/4 NPT F	3/8 F	-	-