

Multi-Line Laser Geo6X

Say hello to the new member of the 6X product family



TECHNICAL DATA	FLG 6X-GREEN
Self-levelling range	± 3°
Accuracy	± 3 mm / 10 m
Laser diode / class	green / 2
Working range* (radius)	30 m
Working range with receiver** (radius)	60 m
Operating time / Power supply	
1 x 360°	12 h / Li-Ion
2 x 360°	9 h / Li-Ion
3 x 360°	7 h / Li-Ion
Dust/waterprotection	IP 54
Temperature range	-10°C - +45°C

*depending on room illumination

**depending on the direction of the laser

FEATURES

- 3 x 360° -Laser lines form 6 laser crosses
- Laser lines switchable separately
- Plumbing function
- Laser plane distance to wall /ceiling min. 12mm
- Wall / tripod mount
- magnets on the back
- strap attachment
- 5/8" and 1/4" tripod connection
- Use with receiver (optional)
- Self-levelling function can be locked for manual use
- 5/8" and 1/4" connection at the instruments bottom

SUPPLIED WITH FLG 6X-GREEN

ART.-NO. 534620

- FLG 6X-GREEN
- Multi-functional mount
- Li-Ion battery
- Charger with USB 3.0 cable
- Padded bag

SUPPLIED WITH FLG 6X-GREEN MAXI-SET

ART.-NO. 534640

- FLG 6X-GREEN
- Li-ion battery
- Charger with USB 3.0 cable
- Lightweight elevating tripod
- Multi-functional mount MH 1
- Adapter WS 1
- Magnetic target green
- Toolbox

