

DUROSTICK KITCHEN & BATH Fungi and mold resistant acrylic paint

PROPERTIES

Highly durable acrylic paint with long lasting protective action. Due to the special fungicidal components contained within its formula, it can protect the film of paint created on the surface as it does not promote nor support mold creation or fungi growth. Suitable to be applied in spaces with intense moisture, and condensations. It is also essential in places with poor ventilation, and lack of natural light. It has excellent resistance to frequent washing. Distinguished for its remarkable coverage, high efficiency and performance. Its properties and abilities make it the ultimate solution for spaces with permanent moisture. Color it in any desired color, through DUROSTICK DUROCOLOR, the measuring system of liquid pigments in 20ml syringe packaging for color creation.

APPLICATIONS

DUROSTICK KITCHEN & BATH acts effectively in spaces such as kitchens and baths, warehouses and basements, as well as the surrounding spaces of heated pools, ceilings with poor thermal insulation etc.

USE

1. Substrate preparation: Surfaces from concrete and marble based plaster have to be dry, at least 30 days after their construction, and free from loose materials.

For new concrete surfaces, make sure to remove any formwork oils using the biodegradable oil cleaner BIOCLEAR (for industrial use). Then, apply two, 1mm thick coat-seach one, of the corrosion inhibitor RUST FREE POWER of DUROSTICK, on any exposed rebars. Once dry, cover the rebars with repair mortar DUROFIX of DUROSTICK. Finally, prime with SOLVENT BASED PRIMER of DUROSTICK, diluted with THINNER 101 or white spirit at a ratio of 1:1.

For new marble based plaster surfaces, sand them down using

#60 sandpaper and prime using 100% ACRYLIC PRIMER, AQUAFIX, micromolar stabilizer or SOLVENT BASED PRIMER of DUROSTICK.

Already painted surfaces require just two coats of DUROSTICK KITCHEN & BATH.

For skimming or spackling, use STUCOFIX-P, POWDER COAT or GRANULAR of DUROSTICK, or any combination of the above, depending on the surface imperfections and smoothness of the finish required. Follow by priming the surfaces.

Surfaces infested with black or green mold or even active fungus, necessarily have to be cleaned using DUROSTICK CLEANER D-95, prior to any other work. Rinse all treated surfaces thoroughly and allow them to dry completely. Once those two necessary steps are concluded, proceed by primed the treated surfaces using AQUAFIX of DUROSTICK.

For peeling surfaces, remove all loose sections and prime using 100% ACRYLIC PRIMER, or AQUAFIX, micromolar stabilizer of DUROSTICK.

Marble based plaster surfaces with severe cracks, are sealed with fast setting repair plaster D-32. Surfaces of concrete are sealed with repair mortar D-55 of DUROSTICK and primed afterwards as described before.

Fill the cracks around door and window casings, by using the paintable ACRYLIC CAULK for indoor use, the elastomeric sealant DUROFLEX-PU of DUROSTICK for outdoor use, or use indoor/outdoor versatile sealant and adhesive, DS-POLYMER, available in 32 colors.

2. Application
Dilute DUROSTICK KITCHEN & BATH with water at a ratio of 5-10%, depending on the substrate, and mix well. Apply with brush, roller or airless spray gun in 2 coats. Apply the second coat, after the first one has fully dried.



Durocolor
MEASURING SYSTEM FOR SHADE RENDERING

TECHNICAL SPECIFICATIONS

Available color	White that does not yellow over time
Colors	20 basic DUROCOLOR liquid pigments in 20ml syringe packaging, that create 120 permanent colors.
Washability	>20.000 cycles (per DIN 53778)
Gloss	Matte
Drying time	1 hour (touch dry), depending on ambient conditions
Recoating time	4-5 hours, depending on ambient conditions
Application temperature	From +8°C to +35°C
Flammable	No

V.O.C. (Volatile Organic Compounds):

Limit value of maximum VOC content per EU (Directive 2004/42/EC) for the particular product (Class A/a: 'Matte coatings for interior walls and ceilings' Type WB): 30 gr/lit (2010). Ready to use product contains maximum 29 gr/lit V.O.C.

NOTE

It is recommended to wash with a soft sponge and mild detergent, all freshly painted surfaces that DUROSTICK BATH & KITCHEN was used, 15 days after application.

CONSUMPTION

1 kg/6-8m² per coat, on properly prepared surfaces.

STORAGE

Store in places protected from sunlight and frost, for up to 18 months from production date.

CLEANING

Clean all tools with water and detergent, immediately after use.

SAFETY DIRECTIONS

The product needs no hazard labeling under current European and national legislation. However, it is recommended to keep the product away from the reach of children. If swallowed seek immediate medical advice and show the container or label.

PACKAGING

Carton box with 12 pcs. of 1kg each one
5kg & 15kg containers

