

# Impact Driver LXT®, DTD173Z

18V, 1/4", 180 Nm, 0 - 3 600 min<sup>-1</sup>

Model DTD173 is a Impact Driver powered by an 18V LXT Li-Ion battery

Feature and Benefits: Slim tool body. Ring illumination LED. Light mode. Compact design with an overall length of 111 mm. Easy to see switch panel. Optimal battery layout. Assist mode



## Technical specifications

Voltage LXT	✓
Nominal Battery Voltage	18 V
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
No load speed	0 - 1100 / 2100 / 3200 / 3600 min <sup>-1</sup>
Max Fastening Torque Impact Drill	20 / 50 / 170 / 180 Nm
Tightening Capacity Standard Bolt	M5 - M16
Capacity machine screw	M4 - M8
Tightening Capacity High Tensile Bolt	M5 - M14
Impacts per Minute (IPM)	0 - 1100 / 2600 / 3600 / 3800 min <sup>-1</sup>
Driving Shank	1/4 "
Sound Power Level (L <sub>WA</sub> )	108 dB(A)
Sound Pressure Level (L <sub>pA</sub> )	100 dB(A)

## User benefits

- Electronic 4 stage impact power selection for added versatility
- Well balanced with a low center of gravity for easy operation
- Slim body design for a good grip
- Electric brake for maximum productivity and increased operator safety
- Anti wobbling bit structure

**EAN 0088381779210**

Link to product - [www.makita.com](http://www.makita.com)



# Related products

## ■ Standard AC

346317-0  
Belt Hook



---

## ■ Other

[User manual](#)

[Parts drawing](#)