

# **TECHNICAL DATA SHEET**

# **Pure acetone**

## **Product description:**

Solvent for paints, lacquers, adhesives, cellulosic resins, acrylic resins etc. It's one of the most used solvents, thanks to its low toxicity and high solvent power. It doesn't affect deep layers of the work, thanks to its high volatility.

# **Operating instructions:**

Dilute the paint until you reach the required fluidity, ideal to obtain the best spreading and lucidity of the product.

#### Advices

It is recommended to do a preliminary test before using the product on the final surface. Avoid release of the product and/or its packaging to the environment.

### Chemical and physical characteristics

Specific weight: 0.798+/- 0.001 g/mL

Flashpoint: < 21°C

Solubility: water-soluble

Product concentration: 99.99% +/- 0.01

Colour: colourless

Physical status: liquid

Odour: distinctive

### **Delivery:**

0,5 lt, 1 lt, 5 lt cans

25 lt drums

1000 lt IBC tank

Kemipol S.r.l. v.le P. Togliatti, 715 00172 Roma CF/PI 00127890689 CCIAA 1513091 sede operativa via Del Commercio, snc 64025 Pineto (TE) Italy T (+39) 085 9461228 info@kemipol.it Azienda certificata

ISO 9001:2015 ISO 14001:2015 OHSAS 18001:2007



www.kemipol.it